
Management console tool

This section provides information about user-specific commands and global setting commands.

User-specific commands

To enroll or edit users, the USER section is used. When the current user does not have administrator rights, the console behavior depends on the security mode of the Fingerprint Software. Secure mode: no commands are allowed. Convenient mode: ADD, EDIT and DELETE commands are possible for standard user. However, the user can modify only his own passport (enrolled with his user name). The following is the syntax:

```
FPRCONSOLE USER command
```

where *command* is one of the following commands: ADD, EDIT, DELETE, LIST, IMPORT, EXPORT.

Table 1. User-specific commands

Command	Syntax	Description
Enroll new user Example: fprconsole user add domain0\testuser fprconsole user add testuser	ADD [<i>username</i> [<i>domain</i> \ <i>username</i>]]	If the user name is not specified, then the current user name is used.
Edit enrolled user Example: fprconsole user edit domain0\testuser fprconsole user edit testuser	EDIT [<i>username</i> [<i>domain</i> \ <i>username</i>]]	If the user name is not specified, then the current user name is used. Note: The enrolled user must verify his fingerprint first.
Delete a user Example: fprconsole user delete domain0\testuser fprconsole user delete testuser fprconsole user delete /ALL	DELETE [<i>username</i> [<i>domain</i> \ <i>username</i> /ALL]]	The /ALL flag will delete all users enrolled on this computer. If the user name is not specified then the current user name is used.
Enumerate enrolled users	List	Lists the enrolled users.

Table 1. User-specific commands (continued)

Command	Syntax	Description
Export enrolled user to a file	Syntax: EXPORT username [domain\username] file	This command will export an enrolled user to a file on the hard disk drive. The user then can be imported using the IMPORT command on other computer or on the same computer, if the user is deleted.
Import enrolled user	Syntax: IMPORT file	The command will import the user from the specified file. Note: If the user in the file is already enrolled on the same computer using the same fingerprints then it is not guaranteed which user will have a precedence in the identification operation.

Global settings commands

The global settings of the Fingerprint Software can be changed by the SETTINGS section. All the commands in this section need administrators rights. The syntax is: FPRCONSOLE SETTINGS *command*

where *command* is one of the following commands: SECUREMODE, LOGON, CAD, TBX, SSO.

Table 2. Global settings commands

Command	Syntax	Description
Security mode Example: To set to convenient mode: fprconsole settings securemode 0	SECUREMODE 0 1	This setting switches between Convenient and Secure mode of the Fingerprint Software.
Logon type	LOGON 0 1 [/FUS]	This setting enables (1) or disables (0) the logon application. If the /FUS parameter is used the logon is enabled in Fast User Switching mode if the computer configuration allows this.
CTRL+ALT+DEL message	CAD 0 1	This setting enables(1) or disables(0) the "Press Ctrl+Alt+Delete" text in logon.
Power-on security	TBX 0 1	This setting globally turns off (0) power-on security support in the fingerprint software. When the power-on security support is turned off no power-on security wizards or pages are shown and it does not matter what are the BIOS settings.

Table 2. Global settings commands (continued)

Command	Syntax	Description
Power-on security single sign-on	SS0 0 1	This setting enables(1) or disables(0) the usage of fingerprint used in BIOS in logon to automatically logon user when the user was verified in BIOS.